

Numerical Simulation of Time Response Section 1.9



Introduction

 So far all of the vibration problems could be represented by linear differential equations of the form:

 Non-linear differential equations do not have such simple solutions:

$$\ddot{\theta} + \frac{g}{I}\sin\theta = 0$$

L

 $m\ddot{x} + k_1x + k_2x^3 = 0$

• These problems can be solved using numerical methods.



The "Euler Method"

- Several numerical methods are available.
 We will use the "Euler Method."
- Assume: dxdt







The "Euler Method"



- As an example, to solve the D.E.: $\dot{x} = ax$
 - then $\frac{x_{i+1} x_i}{\Delta t} = ax_i$ $x_{i+1} = x_i + \Delta tax_i$
- All we **need** is the initial displacement *x*₀ and to choose a good value for Δ*t*. Then we can compute an estimate of *x*(*t*) for each time step.
- The smaller we set ∆t, the better the estimate will be.

West Virginia University.

5

2nd Order Differential Equations

- How about the D.E.: $m\ddot{x} + c\dot{x} + kx = 0$?
- Split it into two problems:
 - $z_1(t) = x(t)$
 - $z_2(t) = \dot{x}(t)$
- Taking derivatives with respect to time:

$$\dot{z}_1(t) = \dot{x}(t) = z_2$$

 $\dot{z}_{2}(t) = \ddot{x}(t) = -\frac{c}{m}\dot{x} - \frac{k}{m}x = -\frac{c}{m}z_{2} - \frac{k}{m}z_{1}$



2nd Order Differential Equations

• In matrix form:



Use Euler equation to solve numerically:

$$\mathbf{Z}_{i+1} = \mathbf{Z}_i + \Delta t \mathbf{A} \mathbf{Z}_i$$



2nd Order Differential Equations

- To use this method, we need to:
 1) Create the A matrix.
 - 2) Initialize $\mathbf{Z}_0 = \begin{vmatrix} x_0 \\ y_0 \end{vmatrix}$
 - 3) Set Δt to a good value.
 - 4) Repeatedly compute $\mathbf{Z}_{i+1} = \mathbf{Z}_i + \Delta t \mathbf{A} \mathbf{Z}_i$

for
$$i = 1$$
 to $\frac{l_{final}}{l}$



8

Other Numerical Methods

 Other, more accurate methods are available, some that even calculate Δt automatically (E.g., Runge-Kutta method).

 These methods are available as functions in Matlab and MathCAD.

Institute of Technology

West Virginia University.

9

Accuracy of Numerical Simulation

m0.1kgx00mωn 3.16228rad/sA0.031623mk1N/mv00.1m/sΦ0rad



Smaller time steps generally yield more accurate solutions.

West Virginia University.

x0 0 rad

0.25 m

9.81 m/s^2

Linearization of Non-Linear System

Now that we know how to get an accurate simulation, let's

compare the numerical ("actual") solution of $\ddot{\theta} + \frac{g}{I}\sin(\theta) = 0$

with the linearized solution $\ddot{\theta} + \frac{g}{I}\theta = 0$.



In this case, the linearization under-predicts the amplitude and period.